Two-Step Position Detection for NIF Automatic Alignment

Presentation to LLNL CASIS Workshop Livermore, California



Abdul Awwal

Automatic Alignment & Imaging Team Integrated Computer Controls System National Ignition Facility (NIF) Lawrence Livermore National Laboratory

November 18-19, 2004

UCRL-PRES-208084

The work was performed under the auspices of the U.S. Department of Energy National Nuclear Security Administration by the University of California Lawrence Livermore National Laboratory under Contract No. W-7405-ENG-48.

Outline




- Introduction
- Problem Statement
- Background
- Two step algorithm examples: simple to complex
- Results
- Challenges



National Ignition Facility








Automatic alignments need automated detection of beam position and automatic mirror adjustments The National Ignition Facility

 Automatic alignment uses video images of fiducials to find positions of laser beam



Problem: How do we detect positions when the fiducials vary in shape and size?




- Automatic alignment needs to detect position of beam
 - Challenges
 - Beams with different markers
 - Same marker, but sizes vary due to defocus
 - Circles of different sizes
 - Variations relatively large

Alignment image contains circles and squares



The National Ignition Facility




Defocused spots exhibit wide variation in size and quality

The National Ignition Facility

Different markers identify different beams






Some alignment images vary from 35 pixels to 200 pixels







Possible solutions



- Centroid
- Template

How to choose the template?

Algorithm background



CMF

$$H_{CMF}(U_x, U_y) = F * (U_x, U_y) = \left| F(U_x, U_y) \right| \exp(\left| \left| j \right| \left| U_x, U_y \right|)$$

POF

$$H_{POF}(U_x, U_y) = \exp(\prod j \prod (U_x, U_y))$$

AMPOF

$$H_{AMPOF}(U_{x}, U_{y}) = \frac{aF * (U_{x}, U_{y})}{\left[b + c |F(U_{x}, U_{y})| + d |F(U_{x}, U_{y})|^{2}\right]^{n}}$$

Position is obtained from cross and autocorrelation and the original template location




 $x_{pos} = x_{cross} \prod x_{auto} + x_c$

$$y_{pos} = y_{cross} \square y_{auto} + y_c$$


CMF output shows cross-correlation location





Problem






Problem



- Two circles, r1 < r < r2 and r3 < r < r4
- Square, d1 < d < d2






- Why ?
- By design
- Due to optics



Two step approach



Step 1: Search for right radius




- Segment based on blob size
 - Segment 1, less than 800
 - Segment 2, between 900 and 1100
 - Segment 3, between 1200 and 1400
- Change to square, repeat step 1

Two step process



Step 2: Find the position



Change to square, repeat step 2

Segmentation is performed based on pixel size




Feature sizes of interest (area in pixels)
 (1086, 1074, 1086, 836, 832, 836)

- Searching for squares (589.0, 158.5)
- Searching for circles at (52.0,158.0)

Movie of the circle match in the correlation plane shows correlation becomes a point at right radius






Correlation is also a circle

Circle becomes smaller as it nears the right radius




Correlation vs radius



Search selected square with dimension of 15.5 pixels



Correlation vs side




square dimension in pixels

Circles of two sizes and squares of a single size detected (after 3 searches and 3 correlations)



The National Ignition Facility




Example 2




- 5 circles, r₁ < r < r₂
 - Where $r_1 = 35$ and $r_2 = 260$

Pinhole images could vary from 35 pixels to 200 pixels (radius)







Solution to complex problem: Example 2



Successive approximation

Centroid

Section the image at centroid

Estimate $r_1 < r < r_2$

Search by matching


Correlate whole edge image with radius range

Find location

Cross-section of images could provide an initial estimate of the radius such as 37 and 204 pixels




The National Ignition Facility




Edge detected image






Two typical final results show the edge and center of the circular images







Refined algorithm



Successive approximation

Segment the image find ROI

Measure the pedestal

Estimate $r_1 < r < r_2$

Search by matching


Correlate segmented image with range of radius

Find location

More detailed in paper no. 5556-30


Box classifier





Search space shows 3 classes, range is chosen to bound the class- box classifier









```
Measure the pedestal area Estimate r_1 < r < r_2
```


```
if (pedestal It 700) then
minRad=5
maxRad=10
elseif (pedestal It 1000) then
minRad=11;
maxRad=22
else
minRad=14;
maxRad=27
end
```


Detection of four defocused spots











Challenges



- Partially missing
- Blobs may be divided into two
- Successive approximation may fail if initial guess is incorrect
 - automated guess correction by counting the right and wrong moves



Acknowledgement



- Wilbert McClay, Jim Candy, Walter Ferguson, Scott Burkhart, Karl Wilhelmsen (Automatic Alignment team)
- Erlan Bliss, Mark Bowers
- Eric Mertens, Patrick J. Opsahl (control room data collection)
- Paul Van Arsdall (feedback)